

# PERFORMANCE BULLETIN

Engine: Yamaha F250XCA /

LF250XCA

**Boat:** Regulator® 26 FS®


Configuration: Twin
Test Date: 2-Mar-2010



#### PERFORMANCE DATA

RPM	МРН	GPH	MPG
1000	6	2.4	2.5
1500	8.5	4.2	2.02
2000	9.9	7	1.41
2500	12.4	10.4	1.19
3000	17.2	14.2	1.21
3500	31.7	16	1.98
4000	37.6	21.4	1.78
4500	43.2	27.5	1.57
5000	48	34.3	1.4
5500	53	42.9	1.24
5900	56.6	49.1	1.15

#### Seconds 0-30 MPH: 5.9



#### NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



### **REGULATOR® 26 FS®**

Length	25' 10"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	5,100 lbs
Maximum HP	500 hp
Fuel Capacity	200 gal
Weight as Tested	8.160 lbs

### F250XCA / LF250XCA

Horsepower	250 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75

## **ENGINE MOUNTING HEIGHT**

Mounting Hole Position #1

# PROPELLER(S)

Series	Saltwater Series II™-SDS™
Diameter x Pitch	15 1/4 x 19
Yamaha Part #	6CE-45970-00-00 / 6CF-45970-00-
	00
Propeller Material	Polished Stainless Steel

#### **TEST CONDITIONS**

Number of People	3	
Air / Water Temperature	42° F / 42° F	
(Fahrenheit)		
Elevation (in feet above sea level)	0'	
Wind Velocity	0-5 MPH	

#### **COMMENTS**

Test weight includes 1/2 tank of fuel, three batteries, T-top, safety and test equipment. Fuel consumption data gathered with Yamaha Command Link® fuel management system. Zero-to-30 speed data gathered with Yamaha speedometer. Other speed data gathered with GPS receiver.

**YPB#:** PB\_REG\_26FS\_t\_F250XCA\_3-2-10\_OCC

## **Boat Manufactured By:**

Regulator

PO Box 49 • Edenton, NC 27932

(252) 482-3837

www.regulatormarine.com

(http://www.regulatormarine.com)

