


Engine: Yamaha F300XCA / F300UCA / LF300XCA Boat: Regulator® 34 CC Configuration: Triple Test Date: 7-May-2014



PERFORMANCE DATA

RPM	МРН	GPH	MPG
1000	7.3	3.9	1.87
1500	10	6.6	1.52
2000	12.3	11.2	1.1
2500	18.8	17.2	1.09
3000	28.7	22.4	1.28
3500	36.2	29.2	1.24
4000	42.1	37	1.14
4500	48.8	47.5	1.03
5000	55.1	63.2	0.87
5500	60.5	74.9	0.81
5850	62.4	78.4	0.8

0-30 MPH: 6.64



NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



REGULATOR® 34 CC

Length	33' 10"
Beam	10' 11"
Dry Weight (Boat Mfr. Pub)	9,528 lbs
Maximum HP	900 hp
Fuel Capacity	350 gal
Weight as Tested	13,596 lbs

F300XCA / F300UCA / LF300XCA

Horsepower	300 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 - 575 - 562 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
Ventilation Plate Height	1 1/2" – 3 1/2" – 1 1/2" Above Boat Bottom

PROPELLER(S)

Series II™-SDS™ (R)
14 3/4 x 22
-45936-00-00 (R)
ned Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature	72° F / 70° F
(Fahrenheit)	72 1770 1
Elevation (in feet above sea level)	0'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 206 gallons of fuel, 4 batteries, safety and test gear. Center engine modified to 35" shaft length for improved performance and efficiency with aftermarket kit in RH rotation.

YPB#: PB_REG_34CC_tri_F300_2014-05-07_OCC

Boat Manufactured By:

Regulator PO Box 49 • Edenton, NC 27932 (252) 482-3837

www.regulatormarine.com

(http://www.regulatormarine.com)

